

Md. Kamal Hossain

Email : dbhossain@yahoo.com

```
C:\WINDOWS\system32\cmd.exe - sqlplus experimento
old 1: insert into min2 values(&empno,'&ename',&sal)
new 1: insert into min2 values(697,'ridoy',2300)

1 row created.
SQL> commit;
Commit complete.
SQL> select * from min1;
  EMPNO ENAME          SAL
-----
    123 kamal          12000
    124 jamal           0
SQL> select * from min2;
  EMPNO ENAME          SAL
-----
    123 kamal          12000
    126 modon           300
    697 ridoy           2300
SQL>
```

Fig: 1 showing Table min1 and min2 datas

```
C:\WINDOWS\system32\cmd.exe - sqlplus experimento
SQL> select * from min2;
  EMPNO ENAME          SAL
-----
    123 kamal          12000
    126 modon           300
    697 ridoy           2300
SQL> desc min1;
Name          Null?    Type
-----
EMPNO         NUMBER(10)
ENAME        VARCHAR2(20)
SAL          NUMBER(8,2)
SQL> desc min2;
Name          Null?    Type
-----
EMPNO         NUMBER(10)
ENAME        VARCHAR2(20)
SAL          NUMBER(8,2)
SQL>
```

Fig : 2 Showing Table structure of Min1 and Min2

Md. Kamal Hossain
Email : dbhossain@yahoo.com

```
Source
Region Source
select * from min2
minus
select * from min1
```

Fig : 3 Showing the Query source using Minus of SQL Report



EMPNO	ENAME	SAL
126	modon	300
697	ridoy	2300

1 - 2

Fig: 4 after running the page I found the result shown.

So, Dear Shapna ,

I didn't find any difficulties using minus in the Query. You can please check out the data type same or not among this two tables.

Thanks.

Md. Kamal Hossain

Email : dbhossain@yahoo.com